



PREMIER CUSTOM SURFACING
RUBBER SAFETY SURFACING | TORONTO, ON | 416-990-8138
WWW.PREMIERCUSTOMSURFACING.COM

MAINTAINING YOUR RUBBERIZED SAFETY SURFACE

Rubberized Safety Surfaces are dependable and resilient by nature but do require minimal maintenance to keep them looking new. Using a pressure washer is the most common procedure for cleaning your rubberized safety surface. Surface should be cleaned following instructions below a minimum of once a year.

WARNING: READ ALL INSTRUCTIONS BEFORE CLEANING

MAINTENANCE AND CLEANING

1. A pressure washer is the recommended method for cleaning the surface. Do not exceed 1500 psi or place the nozzle closer than 12 inches to the surface. Repeat as needed.
2. **For heavily stained areas:** Wet surface and apply a mild household detergent. Scrub thoroughly with a medium bristle brush (do not use a metal or wire brush) Repeat as necessary to completely remove stains.
3. Once the entire surface area has been cleaned, rinse thoroughly using a garden hose.
4. For stubborn or persistent stains contact Premier Custom Surfacing

MINIMUM RECOMMENDED MAINTENANCE

WARNING: READ ALL INSTRUCTIONS BEFORE CLEANING

A. YEARLY MAINTENANCE CLEANING

1. Hose off entire surface to remove food, drink, and loose debris. A pressure washer may be used at a setting not to exceed 1500 psi. Do not place the spray nozzle closer than 12 inches to the surface. Note: Repeat process on an as-needed basis.
2. **ISOLATED STAINS:** On heavily stained isolated spots, while surface is still damp from hosing, apply a sufficient amount of a mild household or commercial detergent for adequate coverage using a hand-held spray bottle. Scrub thoroughly with a 10 inch medium bristle scrub brush. Repeat as necessary on extremely tough stains. It is at the owner's discretion how often to repeat the process on extremely tough stains.



PREMIER CUSTOM SURFACING
RUBBER SAFETY SURFACING | TORONTO, ON | 416-990-8138
WWW.PREMIERCUSTOMSURFACING.COM



PREMIER CUSTOM SURFACING
RUBBER SAFETY SURFACING | TORONTO, ON | 416-990-8138
WWW.PREMIERCUSTOMSURFACING.COM

3. **GENERAL AREA CLEANING:** While surface is still damp from hosing, apply a mixture of full strength mild household or commercial detergent and water using a garden pump sprayer to an area approximately 4 foot by 4 foot in size. Be sure to follow directions for use on the cleaner you choose from your local supplier. Scrub using the 10 inch medium bristle scrub brush. Repeat this process until entire surface has been completely and thoroughly cleansed.
4. Once the entire surface area has been cleaned, rinse thoroughly using a garden hose with attachment.

FOR BEST RESULTS

1. Make sure that area to be cleaned is wet before applying cleansing agent
2. Insure that area is fully rinsed of all cleaning solution after being cleaned.
3. Early morning or late afternoon is the recommended time to clean in order to prevent cleaning solution from drying out before surface is rinsed.
4. Only clean a small area at a time to make sure you don't miss any spots or cause streaking due to unclean areas.
5. It shall be at the owner's discretion whether to remove stains on a less than annual basis. The owner acknowledges that a stain may become more difficult or even impossible to remove if not addressed immediately.



PREMIER CUSTOM SURFACING
RUBBER SAFETY SURFACING | TORONTO, ON | 416-990-8138
WWW.PREMIERCUSTOMSURFACING.COM



PREMIER CUSTOM SURFACING
RUBBER SAFETY SURFACING | TORONTO, ON | 416-990-8138
WWW.PREMIERCUSTOMSURFACING.COM

RECOMMENDED CLEANING AIDS

1. Mild household or commercial detergent (Non-Acid Based)
2. Medium bristle scrub brush, or medium to stiff bristle broom.
3. Garden hose with spray nozzle
4. Pressure washer (1500 psi maximum).

NOTE: The following chemicals can cause potential damage to the surface and should be avoided:

- **Some Disinfectants**
- **Certain Bleach based Pool Cleaners**
- **Pool Shocking Agents**
- **Concentrated Bleach**
- **Weak Acids (Some residential cleaning agents)**
- **Some Organic Solvents**
- **Hot Steam Machines**

Failure to read and follow instructions explicitly will result in damage to the surface and termination of the warranty. Adherence to all of the above requirements will ensure maximum longevity and help maintain the original appearance of your surface. Please contact Premier Custom Surfacing with any questions. **1-877-70PREMIER**



PREMIER CUSTOM SURFACING
RUBBER SAFETY SURFACING | TORONTO, ON | 416-990-8138
WWW.PREMIERCUSTOMSURFACING.COM